



## Safety Data Sheet

Copyright, 2020, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	19-0314-5	<b>Version number:</b>	4.00
<b>Issue Date:</b>	29/03/2020	<b>Supersedes date:</b>	13/09/2015

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

##### Product Identification Numbers

YP-2060-0001-7	YP-2060-0002-5	YP-2060-0003-3	YP-2060-0006-6	YP-2060-0009-0
YP-2060-0014-0	YP-2060-0015-7	YP-2060-0016-5	YP-2060-0017-3	YP-2060-0019-9
YP-2060-0021-5	YP-2060-0022-3	YP-2060-0027-2	YP-2060-0028-0	YP-2060-0029-8
YP-2060-0032-2	YP-2060-0034-8	YP-2060-0035-5	YP-2060-0040-5	

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Immobilisation of upper and lower extremities

For Professional use only.

#### 1.3. Supplier's details

<b>Address:</b>	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
<b>Telephone:</b>	136 136
<b>E Mail:</b>	productinfo.au@mmm.com
<b>Website:</b>	www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 2.

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

DANGER!

### Symbols

Health Hazard |

### Pictograms



### Hazard statements

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system

### Precautionary statements

#### Prevention:

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P285	In case of inadequate ventilation wear respiratory protection.
P280E	Wear protective gloves.
P272	Contaminated work clothing should not be allowed out of the workplace.

#### Response:

P304 + P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P321	Specific treatment (see Notes to Physician on this label).
P314	Get medical advice/attention if you feel unwell.

#### Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

## 2.3. Other assigned/identified product hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

## 2.4. Other hazards which do not result in classification

May be harmful if swallowed.  
Causes mild skin irritation.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Weight</b>
GLASS YARN	65997-17-3	40 - 70
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro- w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	15 - 40
4,4'-methylenediphenyl diisocyanate	26447-40-5	1 - 10
CALCIUM METASILICATE	13983-17-0	1 - 5
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	0.1 - 1

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide.  
Carbon dioxide.  
Hydrogen cyanide.  
Oxides of nitrogen.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Store away from strong bases. Store away from oxidising agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	ACGIH	TWA(inhalable fraction and vapour):2 mg/m3	A4: Not class. as human carcin
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Australia OELs	TWA(8 hours):10 mg/m3	
CALCIUM METASILICATE	13983-17-0	ACGIH	TWA(inhalable fraction):1 mg/m3	
Free isocyanates	26447-40-5	Australia OELs	TWA(as NCO)(8 hours):0.02 mg/m3;STEL(as NCO)(15 minutes):0.07 mg/m3	
Glass filaments	65997-17-3	Australia OELs	TWA(8 hours):0.5 fibers/ml;TWA(as fiber)(8 hours):0.5 fibers/ml	
GLASS YARN	65997-17-3	Manufacturer determined	TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3;TWA(as non-fibrous,	

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

			respirable)(8 hours):3 mg/m3	
--	--	--	------------------------------	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Eye protection not required.

##### Skin/hand protection

Gloves providing sufficient protection must be worn while applying the casting tape. E.g. nitrile gloves with a minimum thickness of 0.127 mm (5 mil, 0.005 inch) have proven to provide effective protection. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

##### Respiratory protection

Results from air sampling during simulated product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use in Health Care facility cast rooms. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations. In general it is recommended to use synthetic casting material in rooms with normal general/dilution ventilation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Roll of Tape. (Fiberglass knitted tape impregnated with moisture curable polyurethane prepolymer resin)
Colour	Multicolour
Odour	Slight Odour
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	No flash point
Evaporation rate	Negligible
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour density	No data available.
Density	1.1 g/ml

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

Relative density	1.1 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	35,000 - 65,000 mPa-s [ @ 23 °C ]
Volatile organic compounds (VOC)	No data available.
Percent volatile	Negligible
VOC less H2O & exempt solvents	No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Sparks and/or flames.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Strong bases.

Amines.

Alcohols.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and

### 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

tightness of chest. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

#### Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Results from air sampling for simulated dry and wet product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations.

Direct contact with the cast surface without the use of gloves should be avoided until curing has completed. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
GLASS YARN	Dermal		LD50 estimated to be > 5,000 mg/kg
GLASS YARN	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Dermal		LD50 estimated to be > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
CALCIUM METASILICATE	Dermal		LD50 estimated to be > 5,000 mg/kg
CALCIUM METASILICATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
BHT - BUTYLATED HYDROXYTOLUENE	Dermal	Rat	LD50 > 2,000 mg/kg
BHT - BUTYLATED	Ingestion	Rat	LD50 > 2,930 mg/kg

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

HYDROXYTOLUENE

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
GLASS YARN	Professional judgement	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Irritant
BHT - BUTYLATED HYDROXYTOLUENE	Human and animal	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
GLASS YARN	Professional judgement	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant
BHT - BUTYLATED HYDROXYTOLUENE	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	official classification	Sensitising
BHT - BUTYLATED HYDROXYTOLUENE	Human	Not classified

**Respiratory Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising

**Germ Cell Mutagenicity**

Name	Route	Value
GLASS YARN	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
CALCIUM METASILICATE	In Vitro	Not mutagenic
BHT - BUTYLATED HYDROXYTOLUENE	In Vitro	Not mutagenic
BHT - BUTYLATED HYDROXYTOLUENE	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
GLASS YARN	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
BHT - BUTYLATED	Ingestion	Not classified for	Rat	NOAEL 500	2 generation



**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

HYDROXYTOLUENE		female reproduction		mg/kg/day	
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
GLASS YARN	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
CALCIUM METASILICATE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
CALCIUM METASILICATE	Inhalation	pulmonary fibrosis	Not classified	Human and animal	NOAEL Not available	
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
BHT - BUTYLATED HYDROXYTOLUENE	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)****Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
GLASS YARN	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
GLASS YARN	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
GLASS YARN	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
GLASS YARN	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Water flea	Estimated	24 hours	EC50	>100 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Zebra Fish	Estimated	24 hours	LC50	>100 mg/l
4,4'-	26447-40-5	Water flea	Estimated		EC50	>100 mg/l

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

methylenediphenyl diisocyanate						
CALCIUM METASILICATE	13983-17-0		Data not available or insufficient for classification			
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Green algae	Experimental	72 hours	Effect Concentration 10%	0.4 mg/l
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Ricefish	Experimental	42 days	NOEC	0.053 mg/l
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
GLASS YARN	65997-17-3	Data not available-insufficient			N/A	
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Data not available-insufficient			N/A	
4,4'-methylenediphenyl diisocyanate	26447-40-5	Estimated Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
4,4'-methylenediphenyl diisocyanate	26447-40-5	Estimated Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

### 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

enyl diisocyanate						
CALCIUM METASILICATE	13983-17-0	Data not available-insufficient			N/A	
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Data not available-insufficient			N/A	

### 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
GLASS YARN	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydroxy-poly(oxy-1,2-ethanediyl)	9048-57-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	26447-40-5	Estimated BCF-Carp	28 days	Bioaccumulation factor	200	Other methods
CALCIUM METASILICATE	13983-17-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BHT - BUTYLATED HYDROXYTOLUENE	128-37-0	Experimental BCF-Carp	56 days	Bioaccumulation factor	1277	OECD 305E - Bioaccumulation flow-through fish test

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional

### 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. During cleanup or disposal of open, uncured product, gloves providing sufficient protection must be worn. E.g. nitrile gloves with a minimum thickness of 0.127 mm (5 mil, 0.005 inch) have proven to provide effective protection. Additionally the following skin protection may be needed: laboratory coat or long-sleeve protective gauntlets.

## SECTION 14: Transport Information

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable

**IERG:** Not applicable.

### International Air Transport Association (IATA) - Air Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

## SECTION 16: Other information

#### Revision information:

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State

<b>3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)</b>
--

regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**